



	OPERATOR MODEL	D	E	F	G	H	K	L	M	N
750mm & 900mm	2200	243	159	264	450	368	273	98	152	72
1050mm	4350	256	154	384	675	457	338	106	191	90

VALVE SIZE	A	B	C	J	P	Q	R	S	AA	AB	AB
750 mm	524	549	914	305	28	1 1/4	984	54	4	1 1/4-7	814 kg
900 mm	616	640	1086	305	32	1 1/2	1168	60	4	1 1/2-6	1143 kg
1050 mm	718	733	1257	305	36	1 1/2	1346	67	4	1 1/2-6	2002 kg

- NOTE 1: FLOW MAY BE IN EITHER DIRECTION
- NOTE 2: VALVE SHAFT WILL MEET OR EXCEED REQUIREMENTS OF SHAFT TABLE PER AWWA STANDARD C-504 FOR APPLICABLE CLASS.
- NOTE 3: REFERENCE AWWA C-504 FLANGES & DRILLING (A.N.S.I. 125)
- NOTE 4: "N" = NUMBER OF TURNS TO CLOSE
- NOTE 5: "P" = NUMBER OF BOLTS ON EACH FLANGE
- NOTE 6: "Q" = DIAMETER OF BOLTS

PROJECT
OWNER
CONTRACTOR
DISTRIBUTOR
CONSULTANT

<b>CLOW CANADA</b>	750mm - 1050mm STYLE 1450 CLASS 150 BUTTERFLY VALVE NON-INDICATING HANDWHEEL OPERATOR FLANGED ENDS	DWG. NO. <b>A-8022</b>
--------------------	--	---------------------------