



| | OPERATOR MODEL | D | E | F | G | H | K | L | M | N |
|---------------|----------------|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 750mm & 900mm | 2200 | 243 | 159 | 264 | 450 | 368 | 273 | 98 | 152 | 72 |
| 1050mm | 4350 | 256 | 154 | 384 | 675 | 457 | 338 | 106 | 191 | 90 |

| VALVE SIZE | A | B | C | J | P | Q | R | S | AA | AB | AB |
|------------|-----|-----|------|-----|----|-------|------|----|----|---------|---------|
| 750 mm | 524 | 549 | 914 | 305 | 28 | 1 1/4 | 984 | 54 | 4 | 1 1/4-7 | 814 kg |
| 900 mm | 616 | 640 | 1086 | 305 | 32 | 1 1/2 | 1168 | 60 | 4 | 1 1/2-6 | 1143 kg |
| 1050 mm | 718 | 733 | 1257 | 305 | 36 | 1 1/2 | 1346 | 67 | 4 | 1 1/2-6 | 2002 kg |

- NOTE 1: FLOW MAY BE IN EITHER DIRECTION
 NOTE 2: VALVE SHAFT WILL MEET OR EXCEED REQUIREMENTS OF SHAFT TABLE PER AWWA STANDARD C-504 FOR APPLICABLE CLASS.
 NOTE 3: REFERENCE AWWA C-504 FLANGES & DRILLING (A.N.S.I. 125)
 NOTE 4: "N" = NUMBER OF TURNS TO CLOSE
 NOTE 5: "P" = NUMBER OF BOLTS ON EACH FLANGE
 NOTE 6: "Q" = DIAMETER OF BOLTS

| |
|-------------|
| PROJECT |
| OWNER |
| CONTRACTOR |
| DISTRIBUTOR |
| CONSULTANT |

| | | |
|--------------------|---|------------------------|
| CLOW CANADA | 750mm - 1050mm STYLE 1450 CLASS 150 BUTTERFLY VALVE | DWG. NO. BFE-15-14D |
| | POSITION INDICATOR HANDWHEEL OPERATOR FLANGED ENDS | |