



	OPERATOR MODEL	D	E	F	H	K	L	M	N
750mm & 900mm	2200	243	159	264	368	273	98	152	72
1050mm	4350	255	154	384	457	338	106	191	90

VALVE SIZE	A	B	C	J	P	Q	R	S	AA	AB	WEIGHT
750	524	540	914	305	28	1 1/4"	984	54	4	1 1/4"-7	814 kg
900	616	640	1086	305	32	1 1/2"	1168	60	4	1 1/2"-6	1143 kg
1050	718	632	1257	305	36	1 1/2"	1346	67	4	1 1/2"-6	2002 kg

NOTE 1: FLOW MAY BE IN EITHER DIRECTION

NOTE 2: VALVE SHAFT WILL MEET OR EXCEED REQUIREMENTS OF SHAFT TABLE PER AWWA STANDARD C-504 FOR APPLICABLE CLASS.

NOTE 3: REFERENCE AWWA C-504 FLANGES & DRILLING (A.N.S.I. 125)

NOTE 4: "N" = NUMBER OF TURNS TO CLOSE

NOTE 5: "P" = NUMBER OF BOLTS ON EACH FLANGE

NOTE 6: "Q" = DIAMETER OF BOLTS

NOTE 7: OPERATED BY 50mm AWWA OPERATING / WRENCH NUT

FIELD ADJUSTABLE SEAT

FUSION BONDED EPOXY COATED IN ACCORDANCE WITH AWWA C550 / NSF 61

PROJECT		
OWNER		
CONSULTANT	DISTRIBUTOR	CONTRACTOR
CLOW CANADA	750mm - 1050mm STYLE 1450 CLASS 150 BUTTERFLY VALVE NON-INDICATING FLANGED ENDS	
	DWG. NO. BFE-15-14C	