



|               | OPERATOR MODEL | D   | E   | F   | H   | K   | L   | M   | N  |
|---------------|----------------|-----|-----|-----|-----|-----|-----|-----|----|
| 750mm & 900mm | 2200           | 243 | 159 | 264 | 368 | 273 | 98  | 152 | 72 |
| 1050mm        | 4350           | 255 | 154 | 384 | 457 | 338 | 106 | 191 | 90 |

| VALVE SIZE | A   | B   | C    | J   | P  | Q      | R    | S  | AA | AB       | WEIGHT  |
|------------|-----|-----|------|-----|----|--------|------|----|----|----------|---------|
| 750        | 524 | 540 | 914  | 305 | 28 | 1 1/4" | 984  | 54 | 4  | 1 1/4"-7 | 814 kg  |
| 900        | 616 | 640 | 1086 | 305 | 32 | 1 1/2" | 1168 | 60 | 4  | 1 1/2"-6 | 1143 kg |
| 1050       | 718 | 632 | 1257 | 305 | 36 | 1 1/2" | 1346 | 67 | 4  | 1 1/2"-6 | 2002 kg |

NOTE 1: FLOW MAY BE IN EITHER DIRECTION

NOTE 2: VALVE SHAFT WILL MEET OR EXCEED REQUIREMENTS OF SHAFT TABLE PER AWWA STANDARD C-504 FOR APPLICABLE CLASS.

NOTE 3: REFERENCE AWWA C-504 FLANGES & DRILLING (A.N.S.I. 125)

NOTE 4: "N" = NUMBER OF TURNS TO CLOSE

NOTE 5: "P" = NUMBER OF BOLTS ON EACH FLANGE

NOTE 6: "Q" = DIAMETER OF BOLTS

NOTE 7: OPERATED BY 50mm AWWA OPERATING / WRENCH NUT

**FIELD ADJUSTABLE SEAT**

**FUSION BONDED EPOXY COATED IN ACCORDANCE WITH AWWA C550 / NSF 61**

|                    |   |            |
|--------------------|---|------------|
| PROJECT            |   |            |
| OWNER              |   |            |
| CONSULTANT         | DISTRIBUTOR   | CONTRACTOR |
| <b>CLOW CANADA</b> | 750mm - 1050mm STYLE 1450 CLASS 150 BUTTERFLY VALVE INDICATING FLANGED ENDS |            |
|                    | DWG. NO. BFE-15-14D   |            |