



	OPERATOR MODEL	D	E	F	G	H	K	L	M	N
750,1050 & 1200	4350	255	154	384	675	457	338	106	190	90

VALVE SIZE	A	B	C	J	P	Q	R	R1	S	AA	AB	WEIGHT lbs
750mm	551	551	997	349	28	44.45	1092	944	76	4	1 3/4-5	1850
1050mm	639	640	1168	355	28	57.15	1270	1109	70	4	2-4 1/2	2600
1200mm	736	759	1340	359	28	57.15	1448	1281	95	8	2-4 1/2	4500

- NOTE 1: FLOW MAY BE IN EITHER DIRECTION
- NOTE 2: VALVE SHAFT WILL MEET OR EXCEED REQUIREMENTS OF SHAFT TABLE PER AWWA STANDARD C-504 FOR APPLICABLE CLASS.
- NOTE 3: REFERENCE AWWA C-504 FLANGES & DRILLING (A.N.S.I. 250)
- NOTE 4: "N" = NUMBER OF TURNS TO CLOSE
- NOTE 5: "P" = NUMBER OF BOLTS ON EACH FLANGE
- NOTE 6: "Q" = DIAMETER OF BOLTS
- NOTE 7: OPERATED BY 50mm AWWA OPERATING / WRENCH NUT
- NOTE 8: RATED AND TESTED FOR 250 PSI WORKING PRESSURE
- NOTE 9: "Z" = (1.59mm RAISED FACE ON EACH FLANGE)

PROJECT
OWNER
CONTRACTOR
DISTRIBUTOR
CONSULTANT

CLOW CANADA	750mm - 1200mm STYLE 1450 CLASS 250 BUTTEFLY VALVE NON-INDICATING HANDWHEEL - FLG x FLG	DWG. No. A-8030
--------------------	---	--------------------