



1757 Burlington St. E.

Hamilton, ON L8N 3R5

PH: 905-548-9604 / 1-800-561-9931

FX: 905-547-0113

[www.clowcanada.com](http://www.clowcanada.com)

## KENNEDY /CLOW ULC/FM 2945A INDICATOR POSTS & INDICATOR POST VALVES STANDARD STOCK MODELS / BURY DEPTHS & GENERAL INFORMATION

MODEL 2945A : The length of bury is the distance measured to the nearest half foot from the bottom of the connecting pipe to the finished grade.

### McAVITY POST INDICATORS

#### MODEL 2945A Weight Lbs

BURY CODE	B	C	D	E
KENNEDY 2945A (BURY RANGE B THROUGH E) TELESCOPING INDICATOR POST (3 - 14" valve) ULC/ FM approved - 60 TURNS MAXIMUM				
<b>WEIGHT &amp; LENGTH</b>	160 lbs / 71" long	190 lbs / 89" long	219 lbs / 107" long	265 lbs / 137" long
<b>size</b>	<b>bury range (ft / metres)</b>	<b>bury range (ft / metres)</b>	<b>bury range (ft / metres)</b>	<b>bury range (ft / metres)</b>
3"	2'5"-4'1" / 0.76-1.25	3'8"-5'6" / 1.16-1.7	5'4"-7' / 1.64-2.13	7'4"-9'4" / 2.25-2.86
4"	2'7"- 4'3" / 0.79-1.30	4'0"- 5'8" / 1.23- 1.73	5'6"- 7'2" / 1.68- 2.18	7'6"- 9'6" / 2.29-2.9
6"	2'11"- 4'7" / 0.89-1.40	4'5"- 6'1" / 1.32- 1.85	5'11"- 7'7" / 1.80- 2.31	7'11"- 9'11" / 2.41- 3.02
8"	3'4"- 5'0" / 1.02-1.52	4'10"- 6'6" / 1.47- 1.98	6'4"- 8'0" / 1.93- 2.44	8'4"-10'4" / 2.54-3.15
10"	3'9"- 5'5" / 1.14-1.65	5'3"- 6'11" / 1.60- 2.12	6'9"- 8'5" / 1.60- 2.57	8'9"- 10'8" / 2.67-3.25
12"	4'1"- 5'9" / 1.24-1.75	5'7"- 7'3" / 1.70- 2.21	7'1"- 8'9" / 2.16- 2.67	9'1"- 11'1" / 2.77-3.38
14"	4'10"-6'6" / 1.47-1.98	6'4"-8'0" / 1.93-2.44	7'10"-9'6" / 2.39-2.89	9'10"-11'10" / 2.99-3.6

INDICATOR POST VALVES /AWWA C509 3 - 12 AWWA C515 14 & LARGER /DUCTILE IRON or CAST IRON CLASS 125 , FLANGED, FF ANSI B16.1(all standard end connections available)/ ULC& FM APPROVED 3- 16" Dia./ EPOXY COATED ULC/FM RATED TO 200 PSI WWP

#### Post Indicator Valves

SIZE	PIV CAST & DUCTILE IRON - TURNS TO FULL	WEIGHT
3"	10.00	78
4"	13.50	103
6"	19.50	150
8"	25.50	228
10"	31.50	385
12"	37.75	539
14"	52.00	700

\*\* Weight is for Flange Valves - other styles weight may be + or - 5%

\*\* NOTE: 16" & LARGER VALVES USE 2945A HD OR HDG INDICATOR POST